

Solid-Body AODD Pumps a Solid Solution for Dangerous Chemicals

KEY CONSIDERATIONS WHEN SELECTING A PUMP TO HANDLE DANGEROUS CHEMICALS, SUCH AS ACIDS, SOLVENTS AND CAUSTICS

By Sergio Avila



Almatec solid-body air-operated double-diaphragm (AODD) pumps represent one of the safest, most durable and effective options for transferring hazardous chemicals.

The use of dangerous chemicals dates back to first century A.D. when the origin and properties of “vitriol” were found in the works of Greek physician Dioscorides and the Roman naturalist Pliny the Elder. Vitriol later became known as sulfuric acid, a highly corrosive mineral acid that is used in automotive applications, mineral processing, fertilizer manufacturing, oil refining and wastewater processing. It is also used in the production of dyes, alcohols, plastics, rubber, ether, glue, film, explosives, drugs, paints, food containers, wood preservatives, soap and detergents, pharmaceutical products, petroleum products, and pulp and paper. Learning how to safely handle such chemicals has been a challenging part of our scientific process for thousands of years.

Sulfuric acid is but one example of the many dangerous chemicals that play a prominent role in manufacturing processes around the world. A chemical that is deemed “highly hazardous” is any substance that is both toxic and reactive, and whose potential for human injury is high if released. The safe containment, handling and transfer of these types of chemicals is critical. There are increasingly strict regulations, certifications and labeling requirements that manufacturers must meet to ensure that distribution

and transfer in the global chemical manufacturing process protects humans and the environment. The transfer of such chemicals requires a highly specialized piece of pumping equipment, and it must be manufactured and operate with these hazardous processes in mind.

Role of Pumps in Chemical Safety

Operators must learn to properly specify equipment based on the application, taking into consideration the unique properties of each dangerous chemical in the process. One example that exemplifies this theory is the Barton Solvents explosion, which occurred at its Wichita, KS, USA, facility in 2007. (VM&P) Naphtha is a flammable liquid that can produce ignitable vapor-air mixtures inside tanks and accumulate dangerous levels of static electricity due to its low electrical conductivity, caused an explosion inside a vertical aboveground storage tank (AST), destroying the tank farm, injuring 11 residents and forcing the evacuation of the town’s 6,000 residents. The U.S. Chemical Safety and Hazard Investigation Board determined that non-conductive flammable liquids capable of forming ignitable vapor-air mixtures inside tanks should be pumped at reduced pumping velocities to minimize the potential for a static ignition.



Personal Protective Equipment (PPE) symbols indicate what must be worn when handling a particular hazardous material, including hand protection, protective clothing and glasses.

Any time a toxic, corrosive or explosive chemical is transferred from one container to another, it poses a very notable threat to the health of workers and the environment. Pipes, valves, seals and connectors are all considered critical transfer components, but pumps are the most critical component. Pumps are used to transfer bulk chemicals from large containers and dispense them into portable containers for shipping to manufacturing or other end-user locations. Pumps also transfer chemicals for blending and dosing applications, among others.

When selecting which pump is ideally suited for handling dangerous chemicals such as acids, solvents and caustics, it is important to consider which pump technology will provide the leak-free operation that is required; which technology has the chemical compatibility for all wetted parts; which pump provides constant flow rates with no slippage; and which technology provides the most reliable operation in harsh conditions or atmospheres.

Comparing Pump Technologies

There are many factors that should go into determining the pump best suited for an operator's dangerous chemical-handling requirements, but seven of the most important factors to consider are:

Leak-free operation

The most important factor in chemical transfer is containment. End-users have to trust that a pump will not only successfully transfer any challenging chemical in its process, but that it will fully contain it, as well. Pumps with mechanical seals are more prone to failure and product leakage than pumps that do not have mechanical seals or packing.

Run dry

In dangerous chemical applications, friction is undesirable and, in certain cases, can be hazardous. When a pump runs dry, that means it continues to run after the chemical has completely passed through it. Where there is no fluid present, internal moving parts will not be lubricated, which can lead to catastrophic failures.

Self-priming

The location in a hazardous chemical application can often be dictated by the safety and convenience to the operator. Strong suction is required in these instances in order to ensure proper flow and transfer rates, which requires a pump that is self-priming.

Materials of construction

Each of the components along the chemical supply chain must be constructed with materials that are compatible with the chemical being handled. For pump equipment, this includes all components on the wetted end, but it is also helpful for the "dry" side of the pump to also have the ability to handle the chemical in the event of an internal seal breakdown or diaphragm rupture.

Shear-sensitivity

When a product is damaged in the pumping process, it is known as "shearing." Substances that require a minimum of agitation are "shear-sensitive." Pumping technologies that have a propensity for shearing are pumps that have meshing teeth or pumps that introduce the fluid to multiple moving parts, such as gear, centrifugal, vane or progressive cavity pumps.

Deadheading

Many chemical applications require a very specific and accurate flow rate to maintain the consistency and quality of the product being handled or manufactured. This can involve valves on the discharge side of the pump that must close quickly, which shuts down flow and causes a jolt to the pump. This process is known as "deadheading." Technologies such as gear and rotary vane pumps need an integral relief valve and a system relief valve to re-circulate fluid back to the source, which means extra piping and, more importantly, the introduction of more heat into the process with the potential for unwanted temperature increases occurring with the liquid.

Ease of maintenance

Maintenance is a key consideration when selecting the right pump technology, no matter the application. However, for pumps in dangerous or hazardous applications, maintenance can be a critical factor due to the elevated safety levels involved when performing any type of maintenance.

Advantages of AODD Pumps

Air-operated double-diaphragm (AODD) pumps represent the safest and most efficient pumping options available when an end-user needs to handle the most dangerous chemicals in their application. AODD pumps are reciprocating, positive-displacement type pumps that only have a few wetted parts and are driven by an air distribution system rather than an electric motor. This allows the pump to run dry and deadhead without damage.

These pumps have no mechanical seal, which eliminates a crucial leak point; provide the superior suction necessary in dangerous chemicals-handling; and are among the safest and most shear-sensitive pumps because the fluid is simply drawn into a chamber and then pushed out with no contact to moving parts within a linear path.

Competitive technologies such as lobe and gear pumps have disadvantages that make them less reliable in handling dangerous chemicals. Lobe pumps, for example, are not true positive displacement pumps, which makes them prone to slipping, which adversely affects flow rates and production volumes. With gear pumps, the meshing gears will begin to wear as soon as the pump is turned on. As gears wear, volumetric consistency is compromised, leading to reduced or inconsistent flow rates and increased energy consumption.

When compared to centrifugal and gear pumps, whose turbulence can damage the particulates present in certain chemical processes, AODD pumps provide a gentle pumping action. There is no friction, which eliminates the “shearing” that can damage or alter the chemical properties. AODD pumps also offer a variety of compatible materials of construction depending on the chemical being used. By removing the need for mechanical seals, AODD pumps also provide virtually leak-free product containment.

The Almatec® Advantage

AODD pumps provide the best solution to dangerous chemicals-handling but not all AODD pumps are created equal. Almatec®, a premier manufacturer of AODD pumps based in Kamp-Lintfort, Germany, offers unique features that other AODD manufacturers do not. These pumps are among the most durable in the industry, and provide operators with consistent performance and a minimum of maintenance requirements. In the chemical industry, few pumps can rival the performance of Almatec’s E-Series line.

Solid Block Construction and Exacting Tolerances

Almatec’s E-Series Plastic AODD pumps are machined from solid plastic block, which increases its strength and life cycle while eliminating many maintenance concerns. The E-Series’ CNC-machined solid block of polyethylene (PE) or

polytetrafluoroethylene (PTFE) allows the pump to deal with the harshest environments. By contrast, competitive pump manufacturers use a plastic injection molding process or lower quality materials. When there is a temperature variation, components can deform and create a potential leak path, no matter how tight the bolts are. However, with Almatec’s solid-block design, there are no crevices where a potential leak



Almatec’s E-Series Plastic AODD pumps are machined from solid plastic blocks of polyethylene (PE) or polytetrafluoroethylene (PTFE), allowing the pumps to handle the harshest environments.

path can be created. It is more robust and the integrity of the material is much stronger due to the high static mass.

Material Compatibility

The E-Series features housing constructed of PE, PTFE, PE conductive and PTFE conductive; EPDM, PTFE/EPDM and NBR diaphragms; EPDM, PTFE, NBR and stainless-steel ball valves; and PTFE cylinder valves. Conductive plastics give the operator peace of mind in explosion-proof zones pumping flammable media or if the pumps are used in an aggressive atmosphere. Although AODD pumps are intrinsically safe, the materials of construction for such applications require conductive materials to properly ground the pump and dissipate electrostatic charges. Almatec’s PE conductive and PTFE conductive E-Series Pumps meet the requirements for the ATEX 94/9/EG directive.

PERSWING P® Air Control System

The PERSWING P® Air Control System offers superior efficiency when comparing flow rate and the air consumption it takes to get to that point, which translates into lower energy costs. It is a lube-free valve with only two moving parts, resulting in a simple, maintenance-free air valve.

Diaphragm and Containment Ring

Almatec offers a unique stainless-steel containment ring. The containment ring enables an enhanced sealing advantage as it helps create consistent high-torque compression all the way around the ring, pulling the components tightly together, compressing the diaphragm, resulting in a leak-free seal. The surface of Almatec diaphragms is smooth and not interrupted by any seals. Due to the integrated metal core, they do not require diaphragm discs that can frequently give rise to leaks and attract dirt.

Pulsation Dampener

The Almatec ET Series pulsation damper is the latest generation of active self-regulating dampers. Its automatic adjustment feature optimizes the diaphragm setting and ensures a consistent flow rate with minimal pulsation and vibration.

Barrier Chamber

The Almatec barrier chamber system meets high safety requirements. The individual diaphragm is replaced by two diaphragms arranged in tandem with a barrier chamber of conductive PE between them and filled with a non-conductive liquid. Given a diaphragm breach, a change in the conductivity within the barrier liquid is detected by sensors and signaled to a controller, which can trigger an alarm, stop air supply to the pump, and/or supply air to a back up pump to prevent process interruption. More importantly, the barrier chamber system prevents media from spilling to atmosphere.

Conclusion

The chemical industry is poised for significant growth as it rebounds from the economic downturn of 2008. According to Cefic Chemdata International, sales were up 26.9% in 2010 compared to 2009, and the industry is projected to continue on that type of sales trajectory. At the same time, technology is driving the creation of new chemical formulations and an even-increasing list of hazardous compounds, which pose a steady diet of new challenges for the manufacturer. The solid-body plastic AODD pump line from Almatec represent the safest, most durable and effective option for

end-users as they protect the health and productivity of their workers and the environment.



Almatec E-Series solid-body AODD pumps are constructed with a containment ring that provides an enhanced sealing advantage, resulting in a leak-free performance.

About the Author:

Sergio Avila is the Almatec Product Specialist with Pump Solutions Group (PSG®). He can be reached at Sergio.Avila@psgdover.com or +1 714-396-1502. Almatec is one of the world's leading manufacturers of air-operated double-diaphragm (AODD) pumps and is an operating company within Dover Corporation's Pump Solutions Group (PSG®). PSG is comprised of several of the world's leading pump brands including Almatec®, Blackmer®, EnviroGear®, Griswold™, Neptune™, Maag®, Mouvex®, Quattroflow™, RedScrew™ and Wilden®. You can find more information on Almatec at www.almatec.de.

Sold Locally by: G&W Industrial Sales

915 Emerson Avenue
Parkersburg, WV 26104
304-422-4755
mail@gwindustrial.com

ALMATEC
A DOVER COMPANY

www.almatec.de

World Headquarters

ALMATEC Maschinenbau GmbH
Carl-Friedrich-Gauß-Straße 5
47475 Kamp-Lintfort
Germany

PSG
PUMP SOLUTIONS GROUP
A DOVER COMPANY