







PV1510 Metal Rubber Fitted

This Brahma™ pump is extremely durable and designed to excel in the most severe operating conditions. The Advanced™ bolted construction provides total product containment and is completely submersible. The Brahma™ pump with its top suction and bottom discharge, large internal clearance and flow through design eliminates clogging. This product is capable of pumping solid laden slurries safely and effectively.

Along with the many features the Brahma™ pump has to offer this pump also comes equipped with the Turbo-Flo™ or Pro-Flo V™ air distribution systems. Both air distribution systems are easy to maintain, efficient to operate and have been proven in utilitarian applications.

Features & Benefits

- Proven Turbo-Flo™ or Pro-Flo V™ ADS
- Durable, Robust Design
- Bolted Construction
- Externally Servicable Air Valve
- Intrinsically Safe Operation
- 51 mm (2") Solids Passage
- 76 mm (3") Solids Passage
- Variable Pressure
- Can Run Dry
- 51 mm (2") or 76 mm (3") NPT or **BSPT inlet & discharge connections**

BAR FEET PSIG 20 [34] 275 120 60 [102] AIR CONSUMPTION (SCFM) [Nm³/h] 250 -100 100 [170] 225 -120 /2041 200 -175 -5-150 -4-125 -100 -75-50 -25-GPM 20 40 60 80 100 120 140 160 180 200 220 240 260 280 300 [LPM] [76] [151] [227] [303] [379] [454] [530] [606] [681] [757] [833] [908] [984] [1060] [1136 **Water Discharge Flow Rates**

与DOVER) c

22069 VAN BUREN STREET • GRAND TERRACE, CA 92313-5607 (909) 422-1730 • FAX (909) 783-3440 www.wildenpump.com

Your Distributor:

G&W Industrial Sales 915 Emerson Avenue Parkersburg, WV 26104 304-422-4755

mail@gwindustrial.com